

# FIELD DATA SCANNING UNIT SE3000 SERIES




SE3000 series scanning units are designed for data logging with a personal computer. The basic unit with 6 input points can be connected to 7 sub units (6 input points / sub unit) and maximum 48 analog data can be collected. Two software packages, "KIDS" for data logging and "PASS" for parameter programming, are available. This unit can be used for input point extension of CHINO's BR series Graphic Recorders.



## ■ Features


### MODBUS protocol

Three kinds of serial communications, RS-232C, RS-422A and RS-485, are standard. The communications protocol is MODBUS for easy system configurations and any specific communications software package is not required.




### Data logging software package

Data can be managed by the data logging software package "KIDS" (separate purchase required) on a personal computer. The logged data can be utilized by worksheet applications.



### Parameter programming software package


Through an engineering port, parameters can be easily set up by the parameter programming software package "PASS" (separate purchase required) from a personal computer.



### Universal input

10 dc voltage/current inputs, 36 thermocouple inputs and 11 resistance thermometer inputs are standard, and ranges can be set to each channel independently.

## ■ System configuration



## ■ Input specifications

Measuring point:	Basic unit 6 points, sub unit 6 points/unit Up to 7 sub units can be connected to one basic unit. (Up to 48 points)
Input kinds:	Universal input (dc voltage, dc current, thermocouple, resistance thermometer)
Accuracy ratings:	Refer to the table of measuring ranges.
Measuring interval:	6-point/1 second, 12-point/2 seconds, 18-point/3 seconds, 24-point/4 seconds, 30-point/5 seconds, 36-point/6 seconds, 42-point/7 seconds, 48-point/8 seconds
Reference junction compensation accuracy:	K, E, J, T, N, Platinel ..... Lower than $\pm 0.5^{\circ}\text{C}$ R, S, Ni-NiMo, AuFe-Cr, WWR5-26, WWR0-26, U, L ..... Lower than $\pm 1.0^{\circ}\text{C}$ (The above error is added to the accuracy ratings for the internal reference junction compensation.)
Burnout:	The sensor disconnection is detected for the thermocouple input and the resistance thermometer input. Burnout enable or disable can be selected in each input.

## ■ Display specifications (Basic unit)

· Status display	
Display element:	Circle type red LED 3 pieces, green LED 1 piece
Display content:	Run status Normal Red LED blinks. Communications status Receiving Green LED lights. Transmitting Red LED lights. Alarm status Activating RED LED lights.
· Data display (option):	5-digit 1 point, Channel shifting/fixed

## ■ Programming specifications (basic unit)

Communications programming:	By DIP switches and sliding switches
Input programming:	By the parameter programming software package "PASS" (separate purchase required) from a personal computer. (For the connection to BR graphic recorders, the input programming can be executed by the BR recorders, too.)

## ■ Alarm specifications (Basic unit)

Alarm point:	Up to 4 points per each channel
Alarm:	High, low, high difference, low difference, high rate-of-change, low rate-of-change
Alarm output:	Not provided

## ■ Safety specifications

CE: EN61326 A1 Class A, EN61010-1 A2

## ■ General specifications

Rated power voltage:	100 to 240VAC, 50/60Hz
Power consumption:	10VA
Operating condition:	· Normal operating condition ... Ambient temperature/humidity 0 to $50^{\circ}\text{C}$ , 20 to 80%RH Power voltage 90 to 264VAC, Power frequency 50/60Hz $\pm 2\%$ · Reference operating condition ... Ambient temperature/humidity 21 to $25^{\circ}\text{C}$ , 45 to 65%RH Power voltage 100VAC $\pm 1\%$ , Power frequency 50/60Hz $\pm 0.5\%$ Altitude Left/right $0^{\circ}$ , forward tilting $0^{\circ}$ , backward tilting $0^{\circ}$ Warming up time More than 1 hour
Casing:	Resin
Weight:	Basic unit 0.6kg, sub unit 0.2kg
Mounting:	DIN rail (35mm)

## ■ Options

Option	Contents
Display unit	Display unit: 7-segment red LED 7-digit Display contents: Channel number 2-digit Data 5-digit Display renewal cycle: 3 seconds

## ■ Accessories (separate purchase required)

Accessories	Contents
KIDS	Data logging software package Windows 95/98/NT4.0/2000
PASS	Parameter programming software package Windows 95/98/NT4.0/2000
Shunt resistor for current input	For 4 to 20mA 250 (1.5W), For 10 to 50mA 100 (1.5W)

## ■ Model

Basic unit (6 input points)

SE310□-000

Display unit (option)  
0: Not provided  
1: Provided


Sub unit (6 input points)

SE3211-000

## ■ Parameter programming software package

“PASS” (separate purchase required) Ver. 4.0 or later

The parameter programming software package “PASS” is for programming parameters of the SE3000.




## ■ Data logging software package

“KIDS” (separate purchase required) Ver. 4.0 or later

The data logging software package “KIDS” is for logging the data measured by the SE3000 and replaying the stored data.

- Data logging by up to 5 sets of SE3000 (up to 100 channels)
- Data logging, replaying, trend graph and report creation
- Stored data for worksheet applications



## ■ General specifications


Input kind	Measuring range	Reference range	Accuracy ratings	Display resolution
DC voltage	-13.8 to 13.8mV	±13.8mV	±0.1% ± 1 digit	10μV
	-27.6 to 27.6mV	±27.6mV		10μV
	-69.0 to 69.0mV	±69.0mV		10μV
	-200 to -200.0mV	±200.0mV		100μV
	-500 to -500.0mV	±500.0mV		100μV
	-2 to 2V	±2V		1mV
	-5 to 5V	±15V		1mV
	-10 to 10V	±10V		10mV
	-20 to 20V	±20V		10mV
	-50 to 50V	±50V		10mV
Thermocouple	K -200 to 300°C	±13.8mV	±0.1% ± 1 digit	0.1°C
	K -200 to 600°C	±27.6mV		0.1°C
	K -200 to 1370°C	±69.0mV		1°C
	E -200 to 200°C	±13.8mV		0.1°C
	E -200 to 350°C	±27.6mV		0.1°C
	E -200 to 900°C	±69.0mV		1°C
	J -200 to 250°C	±13.8mV		0.1°C
	J -200 to 500°C	±27.6mV		0.1°C
	J -200 to 1200°C	±69.0mV		1°C
	T -200 to 250°C	±13.8mV		0.1°C
	T -200 to 400°C	±27.6mV		0.1°C
	R 0 to 1200°C	±13.8mV	±0.15% ± 1 digit	1°C
	R 0 to 1760°C	±27.6mV		1°C
	S 0 to 1300°C	±13.8mV		1°C
	S 0 to 1760°C	±27.6mV		1°C
	B 0 to 1820°C	±13.8mV		1°C
	N 0 to 400°C	±13.8mV		0.1°C
	N 0 to 750°C	±27.6mV		0.1°C
	N 0 to 1300°C	±69.0mV		1°C
	WWR0-26 0 to 2320°C	±69.0mV		1°C
	WWR5-26 0 to 2320°C	±69.0mV		1°C
Resistance thermometer	PR5-20 0 to 1800°C	±13.8mV	±0.2% ± 1 digit	1°C
	PR20-40 0 to 1880°C	±13.8mV		1°C
	Ni-NiMo 0 to 290°C	±13.8mV		0.1°C
	Ni-NiMo 0 to 600°C	±27.6mV		0.1°C
	Ni-NiMo 0 to 1310°C	±69.0mV		1°C
	AuFe-Cr 0 to 300K	±13.8mV	±0.15% ± 1 digit	0.1K
	Platinel -100 to 350°C	±13.8mV		0.1°C
	Platinel -100 to 650°C	±27.6mV		0.1°C
	Platinel -100 to 1390°C	±69.0mV		1°C
	U -200 to 250°C	±13.8mV		0.1°C
	U -200 to 500°C	±27.6mV		0.1°C
	U -200 to 600°C	±69.0mV		0.1°C
	L -200 to 250°C	±13.8mV	±0.1% ± 1 digit	0.1°C
	L -200 to 500°C	±27.6mV		0.1°C
	L -200 to 900°C	±69.0mV		1°C
	Pt100 -140 to 150°C	160	±0.15% ± 1 digit	0.1°C
	Pt100 -200 to 300°C	220		0.1°C
	Pt100 -200 to 850°C	400		0.1°C
	Old Pt100 -140 to 150°C	160	±0.15% ± 1 digit	0.1°C
	Old Pt100 -200 to 300°C	220		0.1°C
	Old Pt100 -200 to 649°C	400		0.1°C
	JPt100 -140 to 150°C	160	±0.15% ± 1 digit	0.1°C
	JPt100 -200 to 300°C	220		0.1°C
	JPt100 -200 to 649°C	400		0.1°C
	Pt50 -200 to 649°C	220	±0.15% ± 1 digit	0.1°C
	Pt-Co 4 to 374K	220		0.1K

Note: The accuracy ratings are under the reference operating conditions. For thermocouple inputs (internal reference junction compensation), the accuracy ratings do not include the reference junction compensating accuracy. The detailed description of the accuracy ratings is separately prepared.

\* The indication may vary to the value of maximum 2mV or in equivalent to 25°C under EMC test environment.


## ■ Terminal board

The figure shown below is the terminal board for the connection with 3 sets of the sub unit (total 24 input points) and with the display unit (option).



## ■ Terminal board

For the connection of 1 basic unit and 3 sub units (total 24 input points), and with the display unit



\* MODBUS is a registered trademark of Schneider Automation Inc., USA. Windows and Windows NT are registered trademarks of Microsoft Corporation, USA.

Products and company names shown in this catalog are trademarks or registered trade marks of their respective companies.

Specifications subject to change without notice. Original 2000.12

## CHINO CORPORATION

32-8, KUMANO-CHO, ITABASHI-KU, TOKYO 173-8632

PHONE: +81-3-3956-2171

FAX: +81-3-3956-0915

E-mail: inter@chino.co.jp

Website: <http://www.chino.co.jp>